





VALVOLE DI SICUREZZA

SAFETY VALVES

The safety valve is a device which allows to establish the minimum pressure of a system by keeping it as integral in case of circuit overpressure.
When pressure inside it practises a higher strenght compared to the spring which holds it as closed, the spring opens by giving fire to the excess-pressure.



Standard supply	Thread from 1/8 to 1"
Material	Brass body CW614N Nbr Seal C98 Spring
Use Temperature	-10°C +90°C / Viton + 250°C
Use	Air - Gas - Steam
Options	V - I
PED Certification	Up to 18 bar

La valvola di sicurezza è un dispositivo che permette di determinare la pressione massima di un impianto e di mantenerlo integro in caso di sovrappressione nel circuito. Quando la pressione all'interno di quest'ultimo esercita una forza superiore a quella della molla che lo tiene chiuso, questa si apre dando libero sfogo alla pressione in eccesso.



Filetto da 1/8 a 1"

Disponibilità standard

Corpo e Dado in Ottone CW614N
Guarnizione in Nbr
Molla in acciaio C98

Materiali

-10°C +90°C / Viton + 250°C

Temperatura di utilizzo

Aria compressa - Gas - Vapore

Impiego

V - I

Opzioni

Fino 18 bar


Certificazione PED

Valvola di sicurezza tarata inamovibile senza certificato
Fixed setting safety valve without certification

Code	F	CH	P	L	Gr.
NVS30018...	1/8	15	6,0	36,0	32,5
NVS30014...	1/4	15	8,0	36,0	35,
NVS30038...	3/8	20	9,0	46,0	73,0
NVS30012...	1/2	22	10,0	46,0	95,0
NVS30034...	3/4	27	11,0	88,0	380,0
NVS3001...	1"	34	16,0	88,0	470,0

Valvola di sicurezza tarata inamovibile categoria IV
Fixed setting safety valve category IV

Code	F	CH	P	L	Gr.
NVS30018...C4	1/8	15	6,0	36,0	32,5
NVS30014...C4	1/4	15	8,0	36,0	35,0
NVS30038...C4	3/8	20	9,0	46,0	73,0
NVS30012...C4	1/2	22	10,0	46,0	95,0
NVS30034...C4	3/4	27	11,0	88,0	380,0
NVS3001...C4	1"	34	16,0	88,0	470,0




Valvola di sicurezza tarata inamovibile con anello senza certificato
Fixed setting safety valve with ring without certification

Code	F	CH	P	L	Gr.
NVS40018..A	1/8	15	6,0	42,0	36,0
NVS40014..A	1/4	15	8,0	42,0	38,0
NVS40038..A	3/8	20	9,0	51,0	76,0
NVS40012..A	1/2	22	10,0	51,0	98,0
NVS40034..A	3/4	27	11,0	98,0	385,0
NVS4001..A	1"	34	16,0	98,0	474,5

Valvola di sicurezza tarata inamovibile con anello categoria IV
Fixed setting safety valve with ring category IV

Code	F	CH	P	L	Gr.
NVS40018..AC4	1/8	15	6,0	42,0	36,0
NVS40014..AC4	1/4	15	8,0	42,0	38,0
NVS40038..AC4	3/8	20	9,0	51,0	76,0
NVS40012..AC4	1/2	22	10,0	51,0	98,0
NVS40034..AC4	3/4	27	11,0	98,0	385,0
NVS4001..AC4	1"	34	16,0	98,0	474,5





Telefono
+39 0445 300499

E-mail
info@unicnet.com

Sito web
www.unicnet.com